

WallBox AC Ensures you pay minimum on every charging

- Collects electricity prices and price area automatic
- · Learns your charging pattern
- Auto-lock opens only for authorized users
- No electrician needed for installation
- · Easy iOS and Android App use and setup
- Premium service program
- Load balancng management
- CE certification done by acredited test institution







ZMARTCHARGE

ZmartCharge App	
Versions	iOS and Android
Electricity Price Area Location	Automatic dedected
Electricity Prices	Automatically collected
Historical Charging	In kWh and price
Guest Access	Unlimited
Chargers that can be controlled	Unlimited

www.ZmartCharge.com

Info@ZmartCharge.com



ZMARTCHARGE

Spend more time with your family. ZmartCharge handles charging!



Specifications

Product Code:WallBox AC> Input Voltage:230V/380Vac±15% - 3 Phase, IT or TN is auto-selected> Rated Current:6~32A> Rated Power:22KW> Power Supply:1, 3 or 3 Phase is auto selected> Charging Type:Level 2> Charging Plug:IEC 62196-2 (Type 2)> Power Plug:CEE Red-5 Pin - 32 A -Adapters for other plugs available.		
Basic Information » Rated Current: 6~32A » Rated Power: 22KW » Power Supply: 1, 3 or 3 Phase is auto selected » Charging Type: Level 2 » Charging Plug: IEC 62196-2 (Type 2)		
 Rated Power: 22KW Power Supply: 1, 3 or 3 Phase is auto selected Charging Type: Level 2 Charging Plug: IEC 62196-2 (Type 2) 		
 » Power Supply: 1, 3 or 3 Phase is auto selected » Charging Type: Level 2 » Charging Plug: IEC 62196-2 (Type 2) 		
 » Charging Type: Level 2 » Charging Plug: IEC 62196-2 (Type 2) 		
» Charging Plug: IEC 62196-2 (Type 2)		
Product Specification » Power Plug: CEE Red-5 Pin - 32 A -Adapters for other plugs available.		
» Power Cable $5x6.0mm^2 + /-0.5mm^2$		
» Charging Cable: 5×6.0 mm ² +/-0.5mm ²		
» Auto start when owner is near		
APP Control		
» Guest access		
» One click change from smart to charge full now		
User Interface » LED Indicator and App		
Communication Interface » OCPP 1.6J; Bluetooth; Wi-Fi and 4G (LTE)		
nart Support» Ensures maximum savings on charging, guest access and dynamic load balancing		
» Working Temp.: -25°C ~ +55°C (-35°C optional)		
» Humidity: 5% ~ 95% Non-Condensing		
Working Environment IP Rate: IP 65 for control box and IP 54 for charging plug		
» Work Altitude: <2000m		
» Body: Thermoplastic; Flame Retardant Grade UL94V-0		
Material Performance		
» Charging Cable: Halogen Free; Pure Copper Core with TPU Cable Jacket		
» Mechanical Life: >10,000 Times		
» Over current protection; Residual current protection; Ground protection	» Over current protection; Residual current protection; Ground protection	
Electrical Protection » Surge protection; Over/Under voltage protection; Over / Under frequency protect	on	
» Over temp protection; Leakage protection Type B (AC 30mA+DC 6mA)		
» Charger Size: L285 × W245 × H88mm		
» Cable Length: 4.5Meter		
Dimension & Package Inner Box: L447 × W337 × H185mm		
» Contains: Charger, Mounting screws, Cable Hanger and user manual		

www.ZmartCharge.com

Info@ZmartCharge.com