






- Collects electricity prices and price area automatic
- · Learns your charging pattern
- Auto-lock opens only for authorized users
- No electrician needed for installation
- Easy iOS and Android App use and setup
- Premium service program
- · Load balancng management
- CE certification done by acredited test institution









Spend more time with your family. ZmartCharge handles charging!

Sp	0		TI	02	TI		n	C
- OL	ᆫ	UI		Ca	ш	u		J

•						
	» Product Code:	WallBox AC				
	» Input Voltage:	230V/380Vac±15% - 3 Phase, IT or TN is auto-selected				
Basic Information	» Rated Current:	6~32A				
	» Rated Power:	22KW				
	» Power Supply:	1, 3 or 3 Phase is auto selected				
Product Specification	» Charging Type:	Level 2				
	» Charging Plug:	IEC 62196-2 (Type 2)				
	» Power Plug:	CEE Red-5 Pin - 32 A -Adapters for other plugs available.				
	» Power Cable	5x6.0mm <sup>2</sup> +/- 0.5mm <sup>2</sup>				
	» Charging Cable:	5×6.0mm <sup>2</sup> +/-0.5mm <sup>2</sup>				
	» Auto start when owner is near					
APP Control	» View historical charging records					
APP COILLOI	» Guest access					
	» One click change from smart to charge full now					
User Interface	» LED Indicator and App					
Communication Interface	e » OCPP 1.6J; Bluetoo	oth; Wi-Fi and 4G (LTE)				
Smart Support	» Ensures maximum savings on charging, guest access and dynamic load balancing					
	» Working Temp.:	-25°C ~ +70°C (-35°C optional)				
Working Environment	» Humidity:	5% ~ 95% Non-Condensing				
Working Environment	» IP Rate:	IP 65 for control box and IP 54 for charging plug				
	» Work Altitude:	<3000m				
	» Body:	Thermoplastic; Flame Retardant Grade UL94V-0				
Material Performance	» Charging Plug Pin:	Pure Copper Silver Plated				
Material Performance	» Charging Cable:	Halogen Free; Pure Copper Core with TPU Cable Jacket				
	» Mechanical Life:	>10,000 Times				
	» Over current protection; Residual current protection; Ground protection					
<b>Electrical Protection</b>	» Surge protection; Over/Under voltage protection; Over / Under frequency protection					
	» Over temp protection; Leakage protection Type B (AC 30mA+DC 6mA)					
	» Charger Size:	L285 × W245 × H88mm				
Dimension & Package	» Cable Length:	4.5Meter				
	» Inner Box:	L447 × W337 × H185mm				
	» Contains:	Charger, Mounting screws, Cable Hanger and user manual				